SEE SHEET 11

SEE DETAIL A THIS SHEET

SEE DETAIL C THIS SHEET

SEE DETAIL D THIS SHEET

SEE DETAIL F THIS SHEET

N89°22'25"W 5284.30' OVERALL
(5238')(R29)
(S89°22'15"E 5283.98')(R23)
(S89°18'E 5268.8')(R1A)(R1B)

2 M&S 34

N89°47'07"E 2616.48'
(2618')(R29)
(N89°46'E 2627.6')(R1)(R1B)
(N89°52'08"E 2618.00')(R10)(R11)
(N89°46'29"E 2616.38')(R23)

N89°44'52"E 2591.36'

1850.14'

741.21'

24 19 25 30

19 20 30 29

20 21 29 28

SEE SHEET 11

SEE DETAIL A SHEET 11

N89°22'26"W 1298.30'
(S89°22'15"E 1298.08')(R23)
(N89°16'35"W

N89°21'42"W 1330.80'
(S89°22'15"E 1330.76')(R23)
2627.76')(R10)

SEE DETAIL B THIS SHEET

N89°22'57"W 1327.63'
(S89°22'15"E 1327.57')(R23)
(N89°16'35"W

N89°22'36"W 1327.57'
(S89°22'15"E 1327.57')(R23)
2655.24')(R10)

N89°47'02"E 1308.26'
(N89°46'29"E 1308.19')(R23)

SEE DETAIL E THIS SHEET

N89°47'11"E 1308.22'
(N89°46'29"E 1308.19')(R23)

COUNTY OF YOLO

(N0°12'E 2656')(R5)
(N01°09'05"E 2656.22')(R10)
(S01°02'26"W 2655.94')(R23)

COUNTY ROAD NO. 104

COUNTY OF YOLO
4 M&S 54

13 M&S 11

Sec 30

1 M&S 9

COUNTY OF YOLO

Sec 29

2 3
LS 4704

FOUND CONTROL MONUMENT PER R23, 5/8" REBAR WITH 2.5" ALUMINUM CAP MARKED AS SHOWN, IN CENTER OF 2.4'x 2.4' CONCRETE SLAB, SOUTH 8.40' & EAST 17.05' FROM CORNER.

(M23, SET YOLO COUNTY MONUMENT IN WELL, 17.05'W. & 8.40'N. TO 1/16 COR)(R23)

ACCEPTED CORNER LOCATION FROM FOUND CONTROL MONUMENT AND DATA PER R23.

4
LS 4704

FOUND CONTROL MONUMENT PER R23, 5/8" REBAR WITH 2.5" ALUMINUM CAP MARKED AS SHOWN, IN CENTER OF 2.4'x 2.4' CONCRETE SLAB, SOUTH 4.56' FROM CORNER.

(SET 2"BRASS DISC IN CONC, STAMPED COY)(R10)

(M4, SET YOLO COUNTY MONUMENT IN WELL, 0.00'W. & 4.56'N. TO 1/4 COR)(R23)

ACCEPTED CORNER LOCATION FROM FOUND CONTROL MONUMENT AND DATA PER R23.

2 6
LS 4704

FOUND CONTROL MONUMENT PER R23, 5/8" REBAR WITH 2.5" ALUMINUM CAP MARKED AS SHOWN, IN CENTER OF 2.4'x 2.4' CONCRETE SLAB, SOUTH 1.01' & EAST 0.23' FROM CORNER.

(M26, SET YOLO COUNTY MONUMENT IN WELL, 0.23'W. & 1.01'N. TO 1/16 COR)(R23)

ACCEPTED CORNER LOCATION FROM FOUND CONTROL MONUMENT AND DATA PER R23.

4 0
LS 4704

FOUND CONTROL MONUMENT PER R23, 5/8" REBAR WITH 2.5" ALUMINUM CAP MARKED AS SHOWN, IN CENTER OF 2.4'x 2.4' CONCRETE SLAB, SOUTH 15.94' & EAST 0.13' FROM CORNER.

(M40, SET YOLO COUNTY MONUMENT IN WELL, 0.13'W. & 15.94'N. TO 1/16 COR)(R23)

ACCEPTED CORNER LOCATION FROM FOUND CONTROL MONUMENT AND DATA PER R23.

(2640-1/2')(R29)
(N01°07'28"E 2637.61')(R10)
(N01°07'28"E 2637.61')(R11)
(N00°59'15"E 2640.22')(R23)

3 7
LS 4704

FOUND CONTROL MONUMENT PER R23, 5/8" REBAR WITH 2.5" ALUMINUM CAP MARKED AS SHOWN, IN CENTER OF 2.4'x 2.4' CONCRETE SLAB, SOUTH 32.25' & WEST 33.78' FROM CORNER.

(REDWOOD POST, 2-1/2' LONG, 4"x 4")(R29)
(1/2"x 5' PIPE)(R1A)
(SET 2"BRASS DISC IN CONCRETE STAMPED COY)(R10)
(MONUMENT DESTROYED, RESET PER RECORD DATA. SET 2"BRASS DISC IN CONCRETE STAMPED LS 3958 & 20/29)(R11)
(FD COY BRASS CAP IN CONC. BOTTOM OF N-S DITCH, S. EDGE E-W DITCH;
M37, SET YOLO COUNTY MONUMENT IN WELL, 33.78'E. & 32.25'N. TO 1/4 COR)(R23)

ACCEPTED CORNER LOCATION FROM FOUND CONTROL MONUMENT AND DATA PER R23.

SOUTH 32.25'
46.70'
S46°19'39"W
WEST 33.78'
FOUND CONTROL MONUMENT.

DETAIL F
NOT TO SCALE

N01°06'04"E 5312.26'
ROW PER 43 DEEDS 622

(N0°12'E 2656')(R5)
(N01°14'53"E 2656.17')(R10)
(S01°09'54"W 2656.28')(R23)

S63°46'19"E 19.07'
SOUTH 8.40'
EAST 17.05'
FOUND CONTROL MONUMENT.

DETAIL A
NOT TO SCALE

SOUTH 4.56'
FOUND CONTROL MONUMENT.

DETAIL B
NOT TO SCALE

5277.66'
5278.24')(R23)
5274.54')(R10)

N01°07'19"E
(N01°07'23"E
(N01°12'41"E

S12°49'44"E 1.04'
SOUTH 1.01'
EAST 0.25'
FOUND CONTROL MONUMENT.

DETAIL C
NOT TO SCALE

S02°15'50"E 17.97'
SOUTH 17.96'
EAST 0.71'
FOUND CONTROL MONUMENT.

DETAIL D
NOT TO SCALE

FOUND CONTROL MONUMENT PER R23, 5/8" REBAR WITH 2.5" ALUMINUM CAP MARKED AS SHOWN, IN CENTER OF 2.4'x 2.4' CONCRETE SLAB, SOUTH 17.96' & EAST 0.71' FROM CORNER.

5
LS 4704

(REDWOOD POST, 2-1/2' LONG, 4"x 4")(R29)
(SET 2"BRASS DISC IN CONCRETE, STAMPED COY)(R10)
(FD 2"BRASS DISC IN CONCRETE STAMPED COY)(R11)
(M5, SET YOLO COUNTY MONUMENT IN WELL, 0.71'W. & 17.96'N. TO SEC COR)(R23)

ACCEPTED CORNER LOCATION FROM FOUND CONTROL MONUMENT AND DATA PER R23.

13 M&S 11

N01°01'30"E 5277.29'
(S00°59-1/2'W 5260.1')(R1)(R1B)

(N01°07'28"E 2636.34')(R10)
(N01°07'28"E 2636.50')(R11)
(N01°02'56"E 2636.89')(R23)

SEE SHEET 13

N
GEODETIC GRID

0' 250' 500' 1000'
SCALE: 1" = 500'

SEE SHEET 1
FOR NOTES AND
BASIS OF BEARINGS.

SEE SHEET 2
FOR LEGEND
AND SHEET INDEX.

SOUTH 15.94'
S00°28'02"E 15.94'
EAST 0.13'
FOUND CONTROL MONUMENT.

DETAIL E
NOT TO SCALE

11 M&S 14

(N89°51'35"E 2626.01')(11PM3)
(N89°45'01"E 2626.08')(R23)
(N89°52'32"E 2625.96')(R33)
N89°46'53"E 2625.39'

25 30 (S89°44'23"E 1325.58')(R23)

(S89°44'23"E 1318.99')(R23)

(S89°44'23"E 1318.96')(R23)

(S89°44'23"E 1318.96')(R23)

30 29

36 31

N89°44'57"W 2644.71'
(S89°41'13"E 2644.49')(R10)(R38)
(S89°41'13"E 2644.69')(R33)
(S89°41'13"E 2644.98')(R17)
(S89°31'E 2644.85')(R5)

N89°44'57"W 2638.09'
(S89°41'13"E 2637.90')(R10)(R19)(R36)(R38)
(S89°41'13"E 2638.09')(R33)

COUNTY ROAD 29

LS 5435 1999 COY

FOUND 5/8" REBAR WITH 1-3/8" PLASTIC CAP MARKED "L 5435", AT SURFACE.
(FD OLD WOODEN STAKE, REPLACED BY 1-1/4"x 36" IRON PIPE)(R5)
(FD 3/4" IRON PIN WITH 1-1/4" HEAD)(R17)
(FD 3/4" IRON PIN WITH 1-1/4" BEVEL HEAD)(R10)
(FOUND 3/4" IRON PIN W 1-1/4 BEVELHEAD STAMPED COY)(R38)
(FOUND IRON PIPE W 1-3/4 FLAT DRIVING HEAD @ SURFACE)(CR8)
(FOUND BUTTONHEAD MONUMENT, DOWN 1.5'; RAISED WITH 5/8"x 18" REBAR LS 5435)(R33)
(FOUND 3/4" IP W/ PLASTIC CAP LS 5532 - DESTROYED - SET 1"x30" IRON PIPE WITH PLASTIC PLUG LS 3752)(CR15)
ACCEPTED MONUMENT LOCATION AS CORNER.

FOUND 2" BRASS DISC IN CONCRETE, MARKED AS SHOWN, AT SURFACE.
(SET 2" BRASS DISC IN CONCRETE STAMPED COY)(R10)
(FD 2" BRASS DISC IN CONCRETE STAMPED COY)(R17)
(1/4 COR PER 11 M&S 83)(R36)
(FOUND CONCRETE MON WITH BRASS DISC STAMPED COY)(R19)(R38)
(RESET COY BRONZE DISK IN CONCRETE ON LINE STAMPED "LS 5435 1999)(R33)
ACCEPTED MONUMENT LOCATION AS CORNER.

31 32

REESTABLISHED CORNER LOCATION ON PROJECTION OF SOUTH LINE OF SECTION 30 AT RECORD DISTANCE PER R33. ALSO FOUND 1-1/4" BRASS DISC IN CONCRETE, WITH TWO PUNCH MARKS, AT SURFACE, N24°40'30"E 18.19' TO CENTRAL PUNCH MARK FROM CORNER.
(FOUND 3/4"IRON PIN WITH 1-1/4" BEVEL HEAD, STAMPED COY)(R10)
(FND NAIL & SHINER N0°54'47"E 30.00')(R36)
(FND STEEL NAIL IN PAVEMENT SET BY YOLO COUNTY OVER MON STAMPED COY)(R19)(R38)
(FOUND CONCRETE NAIL)(R33)
(FOUND NAIL APPROX. INTX CO. RD. 105 & CO. RD. 29. SET 1-1/2" BRASS DISC IN MONUMENT WELL WITH PUNCH MARK.)(CR17)

FOUND 3/4"ID, 1-1/8"OD, IRON PIPE, SLIGHTLY BENT, AT SURFACE, WITH TAG "LS 5435", AS REFERENCE MONUMENT, 30.00' NORTHERLY ON LINE.
(1"IRON PIPE)(R1A)
(SET 1-1/2"IRON PIPE STAMPED COY)(R10)
(FOUND 1-1/2"IRON PIPE STAMPED COY)(R11)
(FD COY BRASS CAP IN CONCRETE IN DITCH BOTTOM)(R23)
(FD 1-1/2"IP, BENT, NORTHERLY ON LINE 30.00')(R33)
(FD 1-1/2"IP, BENT, 0.54 NORTHERLY OF E-W LINE, SET 3/4"x 27"IP LS 5435)(R33)
(SET 3/4"x 27"IP LS 5435 ON LINE NORTHERLY 30.00')(R33)
ACCEPTED REFERENCE MONUMENT. REESTABLISHED CORNER 30.00' SOUTHERLY ON PROJECTION OF LINE.

Yolo County
Book of Maps
2007
Page 206

RECORD OF SURVEY

FOR THE

CONAWAY PRESERVATION GROUP

BEING A SURVEY OF A PORTION OF THAT LAND DESCRIBED IN THE GRANT DEED TO CONAWAY CONSERVANCY GROUP, RECORDED AS DOCUMENT No. 2004-57398, OFFICIAL RECORDS OF YOLO COUNTY;
LOCATED IN PORTIONS OF SECTION 36, TOWNSHIP 10 NORTH, RANGE 2 EAST; SECTIONS 31 & 32, TOWNSHIP 10 NORTH, RANGE 3 EAST;
SECTIONS 1, 12, 13, & 24, TOWNSHIP 9 NORTH, RANGE 2 EAST; AND SECTIONS 5, 6, 7, 8, 9, 16, 17, 18, 19, 20, 21, 22, 27, 28, 29, 33, & 34, TOWNSHIP 9 NORTH, RANGE 3 EAST, MOUNT DIABLO MERIDIAN.

COUNTY OF YOLO, STATE OF CALIFORNIA

MACKAY & SOMPS
CIVIL ENGINEERS, INC.
SACRAMENTO, CALIFORNIA (916) 929-6092

DECEMBER 2007

7891-00